

# Technical Data

## PUROL™ Spray Grease

3H direct food contact, multifunctional, EP grease in an aerosol



Nonfood Compounds  
Program Listed: H1  
ISO 21469 Certified

### Description

ROCOL® PUROL™ Spray Grease is a white, non-toxic lubricant designed for the effective lubrication and protection of seals, guides, bearings and blades particularly those operating in food, pharmaceutical and other clean environments where direct food contact is inevitable.

PUROL Spray Grease is particularly suitable for seals, mincer plates, mixers and slicers where food contact cannot be avoided.

PUROL is manufactured under controlled conditions necessary for the production of a 3H full food contact lubricant.

### Applications

- Seals
- Mincers
- Blades
- Bearings
- Slides
- Bushes

### Approvals / Specifications

- Does not contain: mineral hydrocarbons, animal derived materials, nut oils or genetically modified ingredients.
- Manufactured from only FDA listed ingredients:
  - FDA Group 21 CFR 178.3570
- NSF 3H registered – 148930
- NSF H1 registered – 148930
- ISO 21469
- Halal certified
- Kosher certified
- Vegan Society Approved
- Rocol unique TPM number – 53

### Features & Benefits

- Offers an excellent wide temperature resistance of -10°C to +110°C'
- NSF 3H registered for where food contact is inevitable.
- High load carrying – Excellent EP performance with a 4-ball weld load of 355 kg.
- DETEX - Cartridge has metal detectable plastic components (end caps) capable of detection by most metal detection equipment.
- Good oxidation stability resulting in extended relubrication intervals and a reduction in lubricant usage.
- Aerosol can for convenient application

### Directions For Use

Shake the can thoroughly before spraying.

Hold can upright and apply from a distance of 15-30 cm (6-12 inches).

Should not be mixed with any other lubricant as cross contamination may void the 3H registration. All traces of any previous lubricants should be removed prior to application.

The storage temperature should be kept below +50°C, and the storage area should be out of direct sunlight.

Shelf life is 3 years from date of manufacture.

### Further Information

For pack sizes, part codes and safety data sheets please visit [www.rocol.com](http://www.rocol.com) or get in touch with our customer service team who will be happy to help: [customer.service@rocol.com](mailto:customer.service@rocol.com)

# Technical Data

## PUROL™ Spray Grease

3H direct food contact, multifunctional, EP grease in an aerosol



Nonfood Compounds  
Program Listed: H1  
ISO 21469 Certified

Property	Test Method	Result
Appearance	Visual	White grease
NLGI No.	IP50 – ASTM D217	2
Base Type	N/A	White oil
Base Fluid Viscosity at 40°C	IP71 – ASTM D445	100cSt
Thickener	N/A	Non-soap
Solids	N/A	White, non-toxic solids
Solvent	N/A	Hydrocarbon
Propellant	N/A	LPG (hydrocarbon)
Temperature Range	N/A	-10°C to +110°C
4-Ball Weld Load	IP239 – ASTM D2596	355kg
Copper Corrosion Test	IP112 – ASTM D130	1b

Values quoted above are typical and do not constitute a specification.

Issue 3 Date: 12/21

T +44 (0) 113 232 2600 F +44 (0) 113 232 2740  
E customer.service@rocol.com www.rocol.com  
ROCOL House, Swillington, Leeds LS26 8BS

ROCOL® A division of ITW Ltd

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.

